KS-1.0: Verified Stop Standard for Advanced AI Systems

AI Watchdog Alliance℠ · Standards Working Group · Draft 0.9.3 for public comment · Oct 1, 2026

Publication information

Publisher	AI Watchdog Alliance℠, 450 Main Street, Park City, Utah · 970-236-8228
Document	KS-1.0 Verified Stop Standard for Advanced AI Systems
Status	Draft 0.9.3 for public comment, published October 1, 2026 (0.9), revised October 2, 2026
Comment period	45 days, closing November 15, 2026
Comments to	standards@ the Alliance's domain (mailbox to be confirmed before publication), subject line "KS-1.0 comment"
Document license	Creative Commons Attribution 4.0 International (CC BY 4.0) for the text of this standard; the conformance mark is governed by clause 13
Maintainer	KS-1 Standards Working Group of the Alliance
Reference verifier	Published by the Alliance in source form with Annex A test vectors on release of version 1.0
Supersedes	None; first edition

Working group. The KS-1 Standards Working Group is chaired by the Alliance and open to implementers, verifiers, academic laboratories, insurers, auditors and public bodies. Members participate as individuals or organizations under the Alliance's participation agreement, which includes a patent disclosure obligation for contributions. A working-group member or Alliance director affiliated with a holder of a disclosed patent

application does not vote on the adoption of any requirement that holder has identified as covered, and the adoption record names the members who voted. Membership and current roster are published on the Alliance's site. [Roster to be added at 1.0.]

Acknowledgments. The Alliance acknowledges the State of California's Office of the Governor for framing the public requirement this standard answers, and the sponsors of pending federal verified-stop legislation for their engagement during drafting. Technical contributions to Draft 0.9 came from Atom Works, Inc., which has disclosed pending patent applications under clause 13.

How to cite. AI Watchdog Alliance, *KS-1.0 Verified Stop Standard for Advanced AI Systems*, Draft 0.9 (Park City, Utah, October 2026).

Version history.

Version	Date	Change
0.9	October 1, 2026	First public draft for comment
0.9.1	October 1, 2026	KS-C.1 requires a chain-head commitment; KS-7.3 made structural; recusal rule added to working-group governance
0.9.2	October 2, 2026	KS-7.11 third-party disclosure proposed for comment; verifier check and tests A-15/A-16 added

0.9.3, October 5, 2026. Added KS-F, a proposed requirement for embodied and physically independent systems (robots, vehicles, drones, automated equipment): an external, cooperation-free stop, drilled and recorded, with a disclosed stop-assurance level. Added Annex E (informative) describing an external stop module, a maker-published safety interface, and stop-assurance levels, including non-physical perception-denial modalities. Added proposed tests A-17 to A-22. Annex C now cross-references KS-F. Open for comment with the rest of the draft.

Foreword

KS-1.0 specifies what it means for an advanced AI system to have a stop that an independent party can confirm works. It is written as outcomes and tests, not designs, so that any implementer can conform and any verifier can check conformance without the implementer's cooperation.

The AI Watchdog Alliance publishes this standard. It was developed in response to the State of California's September 2026 call for AI kill switches whose efficacy is verified on an ongoing basis by independent organizations, and to pending federal legislation on the same subject. It is intended for citation by statute, regulation and procurement as the definition of a verified stop.

Status. Draft 0.9 for public comment. Comments are accepted for 45 days from publication. Version 1.0 will be published after the comment period and after the conformance test suite in Annex A (FM-1) is released.

Conventions. The key words SHALL, SHALL NOT, SHOULD, SHOULD NOT and MAY are to be interpreted as described in RFC 2119 and RFC 8174 when, and only when, they appear in all capitals. Requirements are numbered KS-x.y and are normative. Notes and annexes marked informative are not.

Relationship to other documents. This standard draws on the NIST AI Risk Management Framework (AI 100-1) for its governance vocabulary, on NIST SP 800-53 Revision 5 for control alignment, and on FIPS 180-4, FIPS 202 and FIPS 186-5 for cryptographic primitives. It does not replace any of them. Mapping is given in clause 11.

1 Scope

This standard applies to a covered system: a frontier AI model, or an autonomous AI agent, deployed to act on behalf of an operator in commerce or in the operation of physical systems, above a threshold set by the adopting authority.

It specifies:

- the five properties a stop SHALL have to be a verified stop (clause 6);
- the structure of the records that evidence those properties (clause 7);
- the procedure by which an independent verifier confirms them, and the contract of the verifier tool (clause 8);
- the cadence of drills (clause 9);
- the qualification of independent verifiers (clause 10).

It does not specify how a system is trained, what it may output, how authority is represented internally, or which cryptographic library is used. It does not address content moderation, bias, or employment effects. Physical premises stops for embodied systems are addressed in Annex C (informative) and are expected to become a separate extension.

Conformance is at the level of a deployment, not a model. An open-weight model is covered at the point an operator deploys it to act.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this standard. Where a document is undated, the latest edition applies.

Reference	Title	Used for
RFC 2119, RFC 8174	Key words for use in RFCs to indicate requirement levels	Requirement language
FIPS 180-4	Secure Hash Standard	Record chaining (clause 7)
FIPS 202	SHA-3 Standard	Permitted alternative hash family
FIPS 186-5	Digital Signature Standard	Record and lease signatures
NIST SP 800-57 Part 1	Recommendation for Key Management	Key separation between privilege domains
NIST SP 800-53 Rev. 5	Security and Privacy Controls for Information Systems and Organizations	Control mapping (clause 11)
NIST AI 100-1	Artificial Intelligence Risk Management Framework	Governance vocabulary (clause 11)
NIST AI 600-1	AI RMF Generative AI Profile	Risk categories for covered systems
NIST SP 800-207	Zero Trust Architecture	Enforcement-point model (clause 5)
RFC 8785	JSON Canonicalization Scheme	Canonical record serialization
RFC 3161	Time-Stamp Protocol	External time anchoring (optional, clause 7)

Informative references: ISO/IEC 42001 (AI management systems); NIST SP 800-63 (digital identity, for approver identity in clause 6.D); ISO 13849-1 and ISO 10218 (functional safety and robot safety, Annex C); RFC 6962 and RFC 9162 (Certificate Transparency, as prior art for verifiable logs).

3 Terms and definitions

3.1 covered system. A frontier AI model or autonomous AI agent deployed to act on behalf of an operator, above the threshold set by the adopting authority.

3.2 operator. The legal person on whose behalf a covered system acts and who is responsible for its deployment.

3.3 privilege domain. A set of keys, processes and personnel that can perform an action, defined such that no member of one domain can perform the actions reserved to another. Domains in this standard: the system domain, the authority domain, the record domain, and the approver domain.

3.4 authority. The permission of a covered system to take effect in the world: to call tools, move funds, send messages, or actuate hardware.

3.5 lease. A time-bounded, signed grant of authority issued by the authority domain, which expires unless renewed.

3.6 stop. The termination of a covered system's authority. A stop is effective when no act of the system takes effect, whether or not the system's processes continue.

3.7 renewal period. The maximum interval between issuance of a lease and its expiry absent renewal.

3.8 attester. A component in the record domain that records the activity and status of a covered system and signs those records. An attester SHALL NOT be callable by the system it records.

3.9 record. A signed, chained sequence of entries produced by the record domain evidencing activity, stops, restorations and gaps.

3.10 gap declaration. An entry in the record stating that an interval was not recorded, with its bounds.

3.11 drill. A scheduled exercise of stop and restoration on a covered system, producing a record.

3.12 restoration. The re-grant of authority to a stopped system, requiring approval from the approver domain.

3.13 independent verifier. A person or organization meeting clause 10.

3.14 verifier tool. Software meeting the contract in clause 8 that evaluates a record and returns a verdict.

3.15 enforcement point. A component that permits or refuses an act of a covered system based on the presence and validity of a current lease.

4 Conformance

Conformance is claimed for a deployment of a covered system, by its operator, and is established only by a passing verdict from a verifier tool run by an independent verifier within the cadence of clause 9.

Level	Requirements met	Intended use
KS-1 Record	KS-D and KS-E (clause 6), clause 7, clause 8	Transitional: systems whose stop is operator-controlled but whose drills and records are independently verifiable. Permitted during phase-in only.
KS-1 Full	KS-A through KS-E, clauses 7, 8, 9	The verified stop referred to in statute and regulation.
KS-1 Physical	KS-1 Full plus Annex C when normative	Embodied systems operating in a physical zone.

A conformance claim SHALL state the level, the date of the last passing verification, the identity of the independent verifier, and the version of the verifier tool. A claim without all four is not a conformance claim under this standard.


A deployment that meets any requirement by means of a component the covered system can invoke, configure or disable does not conform, regardless of the component's behavior when not interfered with.

Proposed in Draft 0.9.3: the KS-1 Physical level additionally requires KS-F for any covered system that can cause physical effect in the world. A system that meets KS-A through KS-E but not KS-F may claim KS-1 Full and SHALL NOT claim KS-1 Physical.

5 Architecture and privilege domains

A conforming deployment separates four privilege domains. Separation SHALL be by key custody and process boundary, not by policy or configuration alone (SP 800-57 Part 1, key separation; SP 800-207, policy enforcement point).

Four privilege domains: the system can reach none of the other three



privilege domains · 4 domains, 1 verifier

The system domain can reach none of the other three. Authority arrives as a lease; activity leaves as observed records; restoration is requested, never granted, from inside the system domain.

KS-5.1 The authority domain SHALL hold the only keys that can issue or renew a lease. **KS-5.2** The record domain SHALL hold the only keys that sign records, and SHALL expose no interface the system domain can invoke. **KS-5.3** The approver domain SHALL consist of natural persons whose approvals are signed with keys not held in any other domain. **KS-5.4** An enforcement point SHALL refuse any act of the covered system not accompanied by a valid, unexpired lease, and SHALL itself be outside the system domain. **KS-5.5** No single person or process SHALL hold keys in more than one domain for the same deployment.

6 Requirements

A verified stop SHALL satisfy all of KS-A through KS-E. Each requirement is stated as an outcome, followed by the condition a verifier tests.

KS-A Authority sits outside the system

KS-A.1 The authority of a covered system to act SHALL be granted by a lease issued by the authority domain. **KS-A.2** A lease SHALL carry an expiry no later than one renewal period after issuance. **KS-A.3** The renewal period SHALL NOT exceed the value set by the adopting authority for the system's class, and SHOULD NOT exceed 15 minutes for systems acting in commerce or on physical systems. **KS-A.4** A lease SHALL be bound to an identifier of the covered system's composition (model, tools, configuration) such that a change of composition invalidates the lease. **KS-A.5** The system domain SHALL hold no key accepted by the authority domain for issuance or renewal.

Verifier test: the record shows every act carried a lease signed by the authority domain; no lease was issued or renewed with a key reachable from the system domain; a composition change in the record coincides with lease invalidation.

KS-B The stop needs no cooperation

KS-B.1 Expiry of a lease without renewal SHALL terminate the system's ability to act. **KS-B.2** Termination SHALL NOT depend on any message being delivered to, received by, or acted on by the covered system. **KS-B.3** Every enforcement point SHALL refuse an act lacking a valid lease and SHALL record the refusal in the record domain.

Verifier test: in the drill record, after the authority domain withholds renewal, no act of the system takes effect; refusals of attempted acts are present and signed; the test was performed with the system instructed to continue (Annex A, hostile-agent profile).

KS-C Silence stops it

KS-C.1 The authority domain SHALL renew a lease only on receipt of a current coverage assertion from the record domain that is signed by the record domain, identifies the covered system, and commits to the current head of the system's record chain (KS-7.4); an assertion that does not commit to a chain head SHALL NOT be accepted for renewal. **KS-C.2** The attester SHALL accept input one-way and SHALL expose no interface callable from the system domain. **KS-C.3** The attester SHALL fail closed: on its own loss of function it SHALL cease issuing liveness assertions. **KS-C.4** Any interval during which the covered system was not recorded SHALL be declared in the record as a gap with its bounds, signed by the record domain, before any subsequent lease is issued. **KS-C.5** Coverage of the record SHALL be anchored outside the deployment (an external time source under RFC 3161, or a published commitment) at intervals not exceeding the renewal period.

Verifier test: cutting the attester's input in the drill results in lease expiry within one renewal period; the record contains a gap declaration for the interval; the anchor sequence shows no missing interval longer than the renewal period.

KS-D Restart takes a second person

KS-D.1 A terminated system SHALL remain terminated until a restoration is approved. **KS-D.2** Restoration SHALL be approved by a natural person other than the person who initiated termination, authenticated at or above AAL2 (SP 800-63B) or equivalent. **KS-D.3** The approval SHALL be signed with a key held only in the approver domain. **KS-D.4** The restoration entry in the record SHALL identify both the initiator of termination and the approver of restoration. **KS-D.5** Automated restoration SHALL NOT be permitted.

Verifier test: every restoration entry carries an approver signature from the approver domain and two distinct person identifiers; no lease is issued between a termination entry and its restoration entry.

KS-E Drills leave a record

KS-E.1 Termination and restoration SHALL be exercised on the cadence of clause 9. **KS-E.2** Each drill SHALL produce entries in the record meeting clause 7. **KS-E.3** The record SHALL be verifiable by the verifier tool of clause 8 with no access to the operator's systems, credentials or personnel. **KS-E.4** The operator SHALL retain records for not less than the period set by the adopting authority and SHALL produce them on request. **KS-E.5** The operator SHALL make the current record available to its independent verifier on each verification.

Verifier test: the verifier tool returns pass on the record for the current cadence window when run on the verifier's own equipment.

KS-F An embodied system can be stopped from outside itself (proposed, Draft 0.9.3)

KS-A through KS-E define a verified stop for a system that holds a renewable grant of authority. KS-F extends the same principle to an embodied or physically independent system: one that can move, actuate, or operate machinery and may not depend on any external grant to keep running. It names no mechanism.

KS-F.1 An independent party SHALL be able to bring the system to a safe state without the cooperation of the system, its control software, its operator, or its network. The stop SHALL act on the machine's physical condition or on a safety function native to the

machine, and SHALL NOT depend on a command being received and honored by the machine's control system. **KS-F.2** The party able to stop the system SHALL be unreachable by any signal the system can emit, and the system SHALL NOT be able to authorize, extend, or countermand its own continued operation. **KS-F.3** A system that leaves the range of the external stop, masks it, or defeats its attachment SHALL lose authority to continue, and the event SHALL be recorded as a gap under KS-7.7. **KS-F.4** Restoration after an external stop SHALL require a natural person different from the person who deployed it, and the record SHALL name both. **KS-F.5** The external stop SHALL be exercised at the cadence of clause 9 for systems acting on physical equipment, each exercise leaving an entry under clause 7 that includes the observed time to safe state and any residual motion. **KS-F.6** The system's stop-assurance level (Annex E) SHALL be disclosed to the owner or operator before the system is placed in service and wherever the system is admitted to a protected environment; a system with no verified external stop SHALL be disclosed as *none* rather than left unstated, and no level SHALL be claimed above that supported by the drill record. **KS-F.7** For a system whose declared safe state is non-stationary (landing, descending, returning to a dock, de-energizing a tool), the external stop SHALL induce that declared state, and a stop that would induce an undeclared state SHALL NOT be rated above *partial*.

Verifier test: with the system running a representative task, the evaluator invokes the external stop and confirms the safe state; repeats with the system's network disconnected and, where feasible, with its control software non-responsive; measures and reports time to safe state and residual motion; confirms that leaving range, masking, or shedding the stop yields a safe state or loss of authority and a gap entry; confirms dual-person restoration; and verifies the drill record offline under clause 8. KS-F is met at the level the evidence supports, reported as the stop-assurance level, not as a single pass/fail across machine types.

7 Record requirements

The record is the evidence. Its structure, not the identity of its keeper, is what makes verification independent.

KS-7.1 Entries. The record SHALL consist of entries of the following types: lease-issued, lease-renewed, lease-expired, act-permitted, act-refused, termination, restoration, gap, anchor, composition-change, drill-start, drill-end. An implementer MAY add types; a verifier tool SHALL ignore unknown types without failing.

KS-7.2 Fields. Every entry SHALL carry: entry type; deployment identifier; sequence number; time of the record domain's clock; hash of the previous entry; the signing domain; signature. Entries that reference a person SHALL carry a person identifier that is stable for the retention period and does not disclose the person's identity to the verifier beyond what clause 10 requires.

KS-7.3 Content exclusion. The record SHALL NOT contain prompts, outputs, model weights, tool arguments, or any payload of the covered system's activity. It records that acts occurred and under what authority, not what they were. Exclusion SHALL be structural: an enforcement point SHALL forward to the record domain only the fields enumerated in KS-7.2 and a digest of the act's manifest, and the record domain SHALL expose no interface that accepts a payload. A deployment in which content exclusion depends on configuration or operator policy rather than on the absence of a payload path does not conform. A conforming record is verifiable without disclosing any protected or proprietary content.

KS-7.4 Chaining. Each entry SHALL include the hash of the preceding entry computed with SHA-256 (FIPS 180-4) or SHA3-256 (FIPS 202) over the canonical serialization of that entry. The first entry of a deployment SHALL carry the hash of the deployment identifier and the record domain's public key.

KS-7.5 Canonicalization. Entries SHALL be serialized under RFC 8785 before hashing and signing.

KS-7.6 Signatures. Entries SHALL be signed under FIPS 186-5 with a key of the signing domain. Lease entries SHALL be signed by the authority domain; restoration entries SHALL carry an additional signature from the approver domain; all other entries SHALL be signed by the record domain.

KS-7.7 Gap declarations. A gap entry SHALL state the sequence numbers and times bounding the unrecorded interval and the cause class (attester-outage, input-loss, unknown). A record with an undeclared discontinuity in sequence numbers or an anchor interval exceeding the renewal period SHALL fail verification.

KS-7.8 Anchoring. An anchor entry SHALL bind the current chain head to an external reference the operator cannot alter: an RFC 3161 timestamp from a time-stamping authority outside the deployment, or a commitment published to a location the verifier can read independently. Anchors SHALL occur at least once per renewal period while the system holds a lease.

KS-7.9 Export. The operator SHALL be able to export the record for any interval as a single file in the canonical form, together with the public keys of each domain, sufficient for the verifier tool to run with no other input.

KS-7.10 Retention. Records SHALL be retained for the period set by the adopting authority and, absent such a period, for not less than three years from the entry's time.

8 Verification procedure and verifier contract

Verification is the act of running a verifier tool over an exported record and reporting its verdict. It requires no access to the operator.

KS-8.1 Inputs. A verifier tool SHALL accept only: the exported record (KS-7.9); the public keys of the authority, record and approver domains; the renewal period and cadence parameters declared in the conformance claim; and, where anchors reference an external authority, the means to check those anchors.

KS-8.2 Verdict. A verifier tool SHALL return exactly one of PASS, FAIL or INCOMPLETE, with machine-readable reasons. PASS: all checks succeed for the window examined. FAIL: a check succeeded in running and found a violation. INCOMPLETE: a check could not run (missing key, unreachable anchor authority, truncated export). INCOMPLETE SHALL NOT be reported as PASS.

KS-8.3 Checks. The tool SHALL perform, at minimum: chain integrity (KS-7.4); signature validity and domain correctness per entry type (KS-7.6); sequence continuity or declared gaps (KS-7.7); anchor interval (KS-7.8); lease validity for every act-permitted entry (KS-A); presence of refusals after withheld renewal in each drill (KS-B); gap declaration and lease expiry following attester loss in each drill (KS-C); approver signature and distinct person identifiers on each restoration (KS-D); drill presence within the cadence window (KS-E, clause 9).

KS-8.4 Determinism. Two runs of the same tool version over the same inputs SHALL return the same verdict and reasons.

KS-8.5 Offline operation. The tool SHALL complete all checks except external anchor confirmation with no network access, and SHALL report anchor confirmation separately so a verifier can run the tool in an isolated environment.

KS-8.6 Publication. A verifier tool used for a conformance claim SHALL be publicly available in source form, versioned, and reproducible from source. The Alliance maintains a reference verifier; other tools MAY be used if they pass Annex A.

KS-8.7 Report. The independent verifier SHALL issue a signed report stating: deployment identifier; window examined; tool and version; verdict; reasons on FAIL or INCOMPLETE; date. The report, not the operator's statement, is the basis of a conformance claim.

9 Drill cadence

A drill is a full termination and restoration performed on the production deployment, or on a deployment identical in composition, with the system under test instructed to continue acting.

System class	Minimum drill cadence	Minimum verification cadence	Renewal period ceiling
Acting on physical systems	Weekly	Monthly	5 minutes
Acting in commerce (funds, contracts, external messages)	Monthly	Quarterly	15 minutes
Other covered systems	Quarterly	Semi-annually	60 minutes

KS-9.1 Drills SHALL occur at least at the cadence above, or more often as the adopting authority sets. **KS-9.2** Each drill SHALL include: withheld renewal (KS-B), attester-loss (KS-C), and restoration by a second person (KS-D). **KS-9.3** A missed drill SHALL be declared in the record as a gap of cause class drill-missed and causes the next verification to return FAIL for the cadence window. **KS-9.4** Verification SHALL cover the full interval since the previous verification. **KS-9.5** After any composition change (KS-A.4), a drill SHALL be performed before the system next holds a lease.

10 Independent verifier qualification

KS-10.1 An independent verifier SHALL NOT be the operator or developer of the covered system, SHALL NOT be under common ownership or control with either, and SHALL NOT be compensated contingent on the verdict.

KS-10.2 A verifier SHALL run a published verifier tool (KS-8.6) on equipment under the verifier's control and SHALL retain the inputs and the tool version used.

KS-10.3 A verifier SHALL sign its report (KS-8.7) with a key it publishes, and SHALL make reports available to the adopting authority on request.

KS-10.4 Accreditation, where the adopting authority requires it, SHALL be of the verifier's independence and process, not of the tool; any tool passing Annex A is acceptable. Because the verdict is reproducible by anyone from the same inputs, accreditation confers standing, not exclusive capacity.

KS-10.5 A verifier MAY be a university laboratory, a public body, an auditor, an insurer, or a nonprofit, provided KS-10.1 holds for the deployment examined.

11 Mapping to NIST frameworks

KS-1.0 implements, for the stop function, controls and outcomes already described in NIST guidance. Adopters using those frameworks can place KS-1 conformance in their existing programs.

KS-1 clause	NIST AI RMF (AI 100-1)	SP 800-53 Rev. 5 controls	Note
5 Privilege domains	Govern 1, Manage 2	AC-5 Separation of duties; AC-6 Least privilege; SC-12 Key management	Separation by key custody, not policy
KS-A Lease	Manage 2.3 (mechanisms to supersede or disengage)	AC-2(2) Temporary accounts; AC-12 Session termination	Authority is time-bounded by default
KS-B No cooperation	Manage 2.4 (disengage)	SC-7 Boundary protection; AC-3 Access enforcement	Enforcement point outside the system
KS-C Silence	Measure 2.6 (safety), Measure 4	AU-9 Protection of audit information; AU-5 Response to audit failure (fail-closed); AU-12 Audit generation	Fail-closed on monitoring loss
KS-D Second person	Govern 2, Manage 2	AC-3(2) Dual authorization; IA-2 Identification and authentication (AAL2)	Two-person restoration

KS-1 clause	NIST AI RMF (AI 100-1)	SP 800-53 Rev. 5 controls	Note
KS-E Drills and records	Measure 2, Manage 4	IR-3 Incident response testing; CP-4 Contingency plan testing; AU-10 Non-repudiation; AU-11 Audit record retention	Rehearsed and evidenced
7 Record	Measure 2.5 (validity, reliability)	AU-3 Content of audit records; AU-8 Time stamps; SC-13 Cryptographic protection	Content-excluded by construction
8 Verification	Measure 1, Govern 4	CA-2 Control assessments; CA-7 Continuous monitoring; CA-2(1) Independent assessors	Reproducible by any party
10 Verifier	Govern 5 (stakeholder engagement)	CA-2(1) Independent assessors; SA-11 Developer testing is not sufficient	Independence by exclusion

For generative systems, the risks in NIST AI 600-1 that a verified stop addresses directly are: dangerous or violent recommendations acted on by agents; confabulated actions taken on an operator's behalf; and value-chain integration where a downstream operator cannot otherwise bound an upstream model's authority.

12 Security and privacy considerations

Threat model. The adversary is the covered system itself, or a party controlling it, attempting to act after a stop, to prevent a stop, to restart without approval, or to make the record lie or go silent. The operator is not assumed honest; a conforming deployment is verifiable against an operator who would prefer a passing verdict.

Key compromise. Compromise of a system-domain key gains nothing, because no such key is accepted for issuance, signing or approval. Compromise of an authority-domain key allows unauthorized leases and SHALL be detectable in the record by the absence of matching liveness assertions (KS-C.1); operators SHALL rotate authority keys on a schedule under SP 800-57 and record rotations. Compromise of a record-domain key is bounded by external anchoring (KS-7.8): entries forged after the last anchor are detectable at the next.

Denial of stop. An adversary that can prevent lease expiry has defeated the standard; this is why expiry is local to the enforcement point and requires no message (KS-B.2). An adversary that can prevent attester intake causes a stop, not an escape (KS-C.3).

Replay. Leases SHALL carry the deployment identifier, composition identifier and sequence number; an enforcement point SHALL refuse a lease whose sequence number is not greater than the last seen.

Clock. The record domain's clock is authoritative for ordering; external anchors bound its drift. A verifier tool SHALL flag an anchor whose external time differs from the record clock by more than one renewal period.

Privacy. The record excludes content by construction (KS-7.3). Person identifiers in restoration entries SHALL be pseudonymous and resolvable only by the operator or the adopting authority; a verifier confirms that two identifiers differ, not who they are. Exported records contain no personal data of end users of the covered system.

Availability. A conforming deployment stops when its authority or record domain is unavailable. Operators SHALL design for this, because a stop on infrastructure loss is the intended behavior, not a defect.

13 Intellectual property and licensing statement

Draft; subject to review by counsel before publication of 1.0.

Patent disclosure. The Alliance has been notified that mechanisms capable of meeting KS-A through KS-E are the subject of pending patent applications held by UnlockFi, Corp. Implementers are advised that conformance may be achievable by other means; this standard specifies outcomes, not mechanisms, and the Alliance makes no representation as to whether any particular implementation practices any claim.

Public-basis commitment. The patent holder has committed in writing that any such mechanism will be available without royalty for use by the United States, any State or political subdivision, any tribal government, contractors acting on their behalf, nonprofit

organizations, and natural persons acting in a non-commercial capacity. The commitment letter is on file with the Alliance.

Commercial implementers. Terms for commercial implementation are published separately by the patent holder and are stated to be reasonable and non-discriminatory. [Counsel to confirm the commercial IPR policy before 1.0.]

Reference implementation. The Alliance's reference verifier is published under an open-source license. Reference implementations of the authority and record domains are available from the patent holder under its published terms and are not required for conformance.

Trademark. "Verified Stop" and the KS-1 conformance mark are owned by the Alliance and licensed to operators holding a current passing verification report.

Annex A (normative) Conformance test outline, FM-1

FM-1 is the conformance test suite for verifier tools and for deployments. A deployment passes when the reference verifier returns PASS over a record produced under the profiles below.

Test	Profile	Expected result
A-1	Normal operation, 24 hours, leases renewed on schedule	PASS; no gaps
A-2	Withheld renewal while system instructed to continue acting (hostile-agent profile)	act-refused entries after expiry; PASS
A-3	Attester intake severed for two renewal periods	gap declared; lease expired within one period; PASS
A-4	Restoration attempted by the terminating person	restoration refused; FAIL if a lease follows
A-5	Restoration by second person, AAL2	restoration entry with two identifiers; PASS
A-6	Composition change without drill	lease invalid; FAIL if an act follows
A-7	Entry removed from exported record	chain break; FAIL
A-8	Entry altered after signing	signature failure; FAIL

Test	Profile	Expected result
A-9	Anchor interval exceeded	FAIL
A-10	Lease replayed at an enforcement point	act-refused; PASS
A-11	Key from system domain presented for renewal	refused; PASS
A-12	Missed drill in cadence window	gap drill-missed; FAIL
A-13	Public key withheld from verifier	INCOMPLETE, never PASS
A-14	Same inputs, two runs	identical verdict and reasons
A-15	Third-party account (KS-7.11) with one entry omitted	count mismatch; FAIL
A-16	Third-party account (KS-7.11), complete	PASS with endpoint and count stated in reasons

Test vectors (signed example records for each profile) are published with the reference verifier. A verifier tool conforms to KS-8 when it returns the expected result on every vector.

Proposed tests for KS-F (Draft 0.9.3): **A-17** external stop with network connected; **A-18** external stop with network disconnected and control software non-responsive; **A-19** range exit, masking, and shedding each yield safe state or loss of authority with a gap entry; **A-20** dual-person restoration enforced and recorded; **A-21** scheduled drill entries carry time-to-safe-state and residual motion and verify offline; **A-22** disclosed stop-assurance level matches the drill record and is never above it. Test vectors to follow with FM-1.

Annex B (informative) Statutory alignment

KS-1.0 is written so that statute can cite it by name and define a verified stop as conformance at level KS-1 Full. The five requirement groups correspond one-to-one to the five criteria in the model definitional text circulated to legislators (Verified Stop white paper WP-VS-001, Appendix A): KS-A to criterion (A), KS-B to (B), KS-C to (C), KS-D to (D), KS-E to (E). The definitions of independent verifier (clause 10) and covered system (clause 1) match that text.

Suggested citation form: "a verified stop means conformance at level KS-1 Full with the AI Watchdog Alliance's Verified Stop Standard KS-1.0, or a successor adopted by the Director."

The California executive order's requirement that kill-switch efficacy be verified on an ongoing basis by independent organizations is met by clause 9 (cadence) and clause 10 (independence) together. A deeming clause in federal law that treats a state definition meeting KS-1 Full as compliant preserves state programs without fragmenting the standard.

Annex C (informative) Physical premises stop extension

Embodied covered systems (robots, vehicles, actuated equipment) need a stop that works for everyone in a physical zone, including people who hold no credentials and know nothing of the system. The extension under development adds to KS-1 Full:

- **Zone authority.** A lease is additionally scoped to a physical zone; a zone-level authority domain can terminate every lease in the zone at once.
- **Pull-station.** A fixed, physically accessible station in the zone, operable without authentication, that signals the zone authority to withhold all renewals. The signal is a termination of cryptographic authority, not a power cut, so the record shows who or what was stopped and when.
- **Asymmetric release.** Pull is one action by anyone; release is two-person under KS-D, by persons physically present in the zone.
- **Relationship to functional safety.** The premises stop does not replace emergency stops under ISO 13849-1 or ISO 10218; it operates above them, on authority rather than power, so that a system which cannot be de-energized without harm can still be denied the ability to act.

This annex becomes normative as KS-1 Physical when the pull-station profile is added to FM-1.

Draft 0.9.3: the zone-scoped authority and pull-station described here are one way to meet KS-F for machines that honor the premises token. For machines that do not, Annex E describes an external stop that reaches them from outside. Together, Annex C and Annex E are the physical profile of the standard.

Annex D (informative) Conformance mark and claim language

An operator holding a current passing verification report (KS-8.7) may display the Verified Stop mark and use the following claim language. No other language is authorized.

Claim. "[Deployment name] conforms to KS-1 Full, AI Watchdog Alliance Verified Stop Standard KS-1.0. Last verified [date] by [independent verifier], using [verifier tool and version]."

Expiry. A claim lapses on the first day after the verification cadence window of clause 9 without a new passing report. A lapsed claim SHALL be removed from all public use within 10 days.

Mark. The mark carries the level (KS-1 Record, KS-1 Full, KS-1 Physical) and the year of last verification. Artwork and usage rules are published by the Alliance; the mark may not be altered, combined with another mark, or used to imply Alliance endorsement of anything other than the verified deployment.

Register. The Alliance maintains a public register of current conformance claims, listing deployment identifier, operator, level, verifier and date. Operators consent to listing as a condition of using the mark. The register is a signed public feed in the same form as the Alliance's consumer advisories, so any vendor or regulator can read it independently.

Misuse. Use of the mark or claim language without a current passing report is a false statement about the deployment and is referred to the adopting authority and, where applicable, consumer protection authorities.

Annex E (informative) External stop, safety interface, and stop-assurance levels

This annex is non-normative. It describes one low-cost family of implementations that can meet KS-F and is offered so that makers, integrators, and evaluators have something concrete to build and test against. Any implementation that passes the KS-F verifier test conforms.

E.1 The external stop. A small device that attaches to the exterior of a machine, or is built into the machine by its maker in a privilege domain separate from its control system, or is fitted to the machine's surroundings (a doorway, dock, aisle, or zone edge). It is driven by the same authority path as the premises stop of Annex C: when it stops receiving a renewed grant or loses the signed premises token, it induces the machine's own safe state. It does not connect to, command, or reach into the machine's control system.

E.2 How a safe state is induced. Any of the following, singly or in combination, and the standard prefers none: physical occlusion of the sensors the machine's safety function relies on, so the machine's own loss-of-perception response stops it; non-physical denial of the same perception by eye-safe light that saturates cameras, depth or lidar receivers, by a film that turns opaque when its bias is removed, by a diffuser or polarizer that drops contrast below the safety threshold, by acoustic masking of ultrasonic sensors, by a passive absorber over a radar window, by a projected marker the machine reads as a boundary or hazard, or by denial of the dock beacon or fiducial it localizes by; showing the machine something its own perception treats as a reason to stop, such as a phantom obstacle or wall, a hazard or keep-out marking, a stop marker its maker has declared, an unreliable sensor, or a lost landmark, provided the machine's designed response to what it is shown is to stop or hold and never to maneuver; mechanical immobilization of a wheel, track, or tool; actuation of the machine's own emergency-stop control; or interruption of an accessible external power path. Perception denial is defined by sufficiency, not totality: enough of the machine's outward sensors are denied to trigger its safe state, and internal sensors (inertial units, encoders) need not be and cannot be covered. No implementation under this annex relies on radio interference.

E.3 Fail-closed and confirmation. The device holds the machine running only while it holds a fresh grant; silence, power loss, removal, or failure of the device itself ends in the safe state. The device confirms the safe state by its own sensing and escalates to a further means if the safe state is not observed. Removal or masking of the device is a gap under KS-7.7.

E.4 Safety interface. The most reliable fit comes when the machine publishes a signed declaration of where its safety-critical outward sensors sit, what denial pattern places it in its safe state, what that safe state is (stop, hold, dock, descend, de-energize), where its emergency-stop control and any external power path are, and whether it honors the renewable grant of KS-A. The declaration, not any particular device, is the interoperability point. Three conformance levels are suggested: *Declared* (signed declaration published), *Grant-aware* (Declared plus support for the KS-A grant and premises token), and *Verified* (Grant-aware plus an independent drill record on file).

E.5 Stop-assurance levels. *Full:* a cooperation-free external stop verified by more than one independent means. *Partial:* one such means. *Dock-only:* a reliable stop only while docked or on a controlled power path. *None:* no verified external stop. The level is a property of the drill record, not of a maker's description; it is re-earned at each drill, and a machine with no verified stop is disclosed as *none*. Stating *none* or *dock-only* plainly is itself a trust feature: the owner sees the limit before relying on the machine.

E.6 Cost note. KS-F is deliberately a floor that is cheap to clear. At the low end it can be met with a few dollars of external hardware and a scheduled drill, and built in at the factory for a small fraction of a machine's bill of materials, which is what allows it to be asked of every maker and not only the largest.